Project Name: Kusile Power Station OHS Specification for Coal ASH Limestone and Gypsum Maintenance Services

Enquiry number:

Project Address: Kusile power station, R45 Kendal /Balmoral Road, Haartebeesfontein farm

Eskom Contract's Manager

Name: Thami Simelane

Signature: 

Date: 07/09/2026

Eskom's Health and Safety Manager

Name: Mapuleng Kobo

Signature: pp 

Date: 07.09.2026

Eskom's Procurement Manager

Name: Matshidiso Kgafane

Signature: 

Date: 16 Sep 2026

Eskom's Safety Officer

Name: Nkhetheni Ramukosi

Signature: 

Date: 07/09/2026

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

Table of Contents

1. INTRODUCTION 4

2. SUPPORTING CLAUSES 4

2.1 SCOPE 4
2.1.1 Purpose 4
2.1.2 Applicability 4
2.2 NORMATIVE/INFORMATIVE REFERENCES 5
2.2.1 Normative 5
2.2.2 Informative 5
2.3 DEFINITIONS 6
2.4 ABBREVIATIONS 9
2.5 RELATED/SUPPORTING DOCUMENTS 10

3. DOCUMENT CONTENT 10

3.1 SCOPE OF WORK 10
3.2 EMPLOYER'S REQUIREMENTS FOR THE SERVICE 10
3.3 LEGAL COMPLIANCE 10
3.4 ESKOM KUSILE POWER STATION REQUIREMENTS 12
3.5 SHEQ POLICY 12
3.6 COID 12
3.7 COSTING FOR OHS WITHIN THE PROJECT 12
3.8 STATUTORY APPOINTMENTS 12
3.9 ESKOM KUSILE POWER STATION LIFE-SAVING RULES 13
3.10 SUBSTANCE ABUSE 14
3.11 CONTRACTOR ORGANISATIONAL STRUCTURE 15
3.12 ROLES AND RESPONSIBILITIES 15
3.13 RISK ASSESSMENT (REFER TO 32-520) 19
3.14 SAFE WORK PROCEDURES / METHOD STATEMENTS 20
3.15 ROOF WORK (REFER TO 32- 418) 21
3.16 FIRE EQUIPMENT AND MAINTENANCE 21
3.17 FLAMMABLE, COMBUSTIBLE LIQUIDS AND HAZARDOUS CHEMICAL AGENTS 21
3.18 FIRST AID AND EQUIPMENT 22
3.19 OHS COMMUNICATION SYSTEMS 23
3.20 TOOL BOX TALKS / DAILY TEAM TALKS / PRE JOB MEETINGS 26
3.21 OHS TRAINING 26
3.22 GENERAL TRAINING 27
3.23 CONTRACTOR SITE ESTABLISHMENT 27
3.24 SITE ROADS 28
3.25 VEHICLE MANAGEMENT 28
3.26 HOUSEKEEPING AND ORDER 29
3.27 STACKING AND STORAGE 30
3.28 WORKPLACE SIGNAGE AND COLOUR CODING 30
3.29 TOOLS AND EQUIPMENT 31
3.30 LADDERS 32
3.31 SCAFFOLDING 32
3.32 AUDITING 33
3.33 SMOKING 33
3.34 CELLULAR PHONES 33
3.35 OCCUPATIONAL HEALTH, HYGIENE AND REHABILITATION 34
3.36 ROLES AND RESPONSIBILITIES 36

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

3.37 WORKING AT HEIGHTS 36
3.38 PERSONAL PROTECTIVE EQUIPMENT REQUIREMENTS 37
3.39 CONFINED SPACES 38
3.40 INCIDENT INVESTIGATION 39
3.41 EMERGENCY MANAGEMENT 39
3.42 NON-CONFORMANCE AND COMPLIANCE 39
3.43 OHS FILES 40
3.44 WORK STOPPAGE 40
3.45 HOURS OF WORK 41
3.46 OMISSIONS FROM SAFETY AND HEALTH REQUIREMENTS SPECIFICATION 42
3.47 CONTRACT SIGN OFF 42
3.48 ESKOM KUSILE POWER STATION 'S RIGHT TO TERMINATE THE CONTRACT 42
3.49 BARRICADING 42
3.50 CONTRACTOR PERFORMANCE MONITORING 43

4. AUTHORIZATION 44

5. REVISIONS 44

6. DEVELOPMENT TEAM 44

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

1. Introduction

Eskom Kusile Power Station's responsibility and commitment is to ensure a safe working environment is in line with its Safety, Health, Environmental, and Quality (SHEQ) Policy and applicable legislative obligations. This OHS specification is Eskom Kusile Power Station minimum requirements which are required to be met for the duration of the contract period by contractors/suppliers and, where required, the delivery organisation. The contractor is expected to develop an OHS plan that meets these requirements as well as all the relevant applicable legislation that they conform to. Eskom Kusile Power Station in no way assumes the contractor's legal responsibilities and liabilities. The contractor is and remains accountable for the quality and execution of their health and safety programme for their employees and appointed contractor employees. This OHS specification reflects minimum requirements and should not be construed as all-encompassing.

Note 1: All the requirements listed hereunder are in relation to the contract and do not supersede or replace any organizational OHS requirements.

Where requirements listed are already in place, then the organizational requirements must be taken cognisance of and listed in the respective OHS plans. If there are any additional Eskom Kusile Power Station and/or legislative requirements listed in the OHS specification, then these must be addressed.

2. Supporting Clauses

2.1 Scope

This OHS specification lists the legislative and Eskom Kusile Power Station requirements and, where applicable, any requirements pertaining to local authorities, municipal by-laws, or environmental legislation that must be met by the contractor.

2.1.1 Purpose

This document will provide requirements to ensure compliance to legal and other requirements pertaining to Kusile Power Station Coal, Ash, Limestone and Compressor Plant Electrical Maintenance Services & BMH ERI C&I Maintenance Labour Service & Coal, Ash, Limestone and Gypsum Mechanical Maintenance Services Scope of Work

2.1.2 Applicability

This OHS specification is applicable to any contracting organisation that intends to respond to Station the Kusile Power Station Coal, Ash, Limestone and Gypsum Mechanical Maintenance Services Scope of Work.

tender/enquiry with the intention of entering a contract.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

2.2 Normative/Informative References

Parties using this document shall apply the most recent edition of the documents listed in the following paragraphs.

2.2.1 Normative

[1] Basic Conditions of Employment Act No 75 of 1997.
[2] Occupational Health and Safety Act and Regulations No 85 of 1993.
[3] OHS Act “Regulations on Hazardous Work by Children in South Africa”
[4] National Environmental Management Act 107 of 1998.
[5] National Road Traffic Act 93 of 1996.
[6] 32-37 Eskom Kusile Power Station Substance Abuse Procedure.
[7] 32-136 Contractor Health and Safety Requirements
[8] 240-62196227 Life- saving Rules
[9] 32-95 Occupational Health and Safety Incident Management Procedure
[10] 240-131838225: Occupational Health and Safety Incident Management Definitions and Classification Parameters
[11] 32-727 SHEQ Policy
[12] 32- 418 Working at Heights Procedure
[13] 240-62946386 Vehicle and Driver Safety Management Procedure
[14] 32-520 Risk Assessment procedure
[15] Plant Safety Regulations
[16] BS ISO 45001 :2018 Occupational Health and Safety Management Systems
[17] Eskom Kusile Power Station Covid-19 policy
[18] National Disaster Management Act 57 of 2002
[19] Eskom Personal Protective Equipment 240-44175132
[20] Kusile Power Station Coal, Ash, Limestone and Gypsum Mechanical Maintenance Services KUS-20251084

2.2.2 Informative

[21] Tobacco Products Control Act 83 of 1993 (Updated 2011.05.19)
[22] SANS 1186 Symbolic Safety Signs
[23] SANS 10147 – Inspection of Pressure Equipment
[24] SANS 347 – Categorisation and Conformity Assessment
[25] Act No. 85 of 1993 – Occupational Health and Safety Act (OHS Act and Pressure Equipment Regulation
[26] Constitution of the Republic of South Africa No 108 of 1996
[27] SANS 10234:2019 Global Harmonized System of classification and labelling of Chemicals

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

2.3 Definitions

Definition	Explanation
Appointed Contractor	Means a contractor appointed by the Main contractor
Baseline Risk Assessment	(32-520) baseline operational risks refer to the health and safety risks associated with all standard processes and routine activities in the business
Business Unit (BU)	(32-296) means any defined unit within the Eskom Kusile Power Station environment, operating as a business under a particular cost-centre number. In the context of this document and in terms of health and safety, any reference to a BU includes a defined unit within any Eskom Kusile Power Station division and its subsidiaries
Client	(OHS Act) Eskom Kusile Power Station representative (Internal – Asset Owner), also referred to as the contract administrator/custodian or agent or project manager (as defined in the contract). He/she is the person responsible for ensuring that the works or services are executed in terms of the contract, as well as adherence to legislation pertaining to the contract.
Competent Person	(OHS Act) means any person having the knowledge, training, experience, and qualifications, specific to the work or task being performed, provided that, where appropriate, qualifications and training are registered in terms of the South African Qualifications Authority Act, 1995 (Act No. 58 of 1995)
Contractor	(OHS Act) means an employer as defined in section 1 of the Act who performs contracted work and includes Main contractors
Consultant	means a person providing professional advice
Controlled Disclosure	controlled disclosure to external parties (either enforced by law or discretionary)
Duty of Care to the Environment	(32-136) anybody who causes or has caused or may cause significant pollution or degradation of the environment must take reasonable measures to prevent such pollution or degradation from occurring, continuing, or recurring. If such harm to the environment is authorised by law or cannot reasonably be avoided or stopped, such person must minimise and rectify such pollution or degradation of the environment
Employee	(OHS Act) means, subject to the provisions of subsection (2), any person who is employed by or works for an employer and who receives or is entitled to receive any remuneration or who works under the direction or supervision of an employer or any other person
Employer	(OHS Act) means, subject to the provisions of subsection (2), any person who employs or provides work for any person and

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

Definition	Explanation
	remunerates that person or expressly or tacitly undertakes to remunerate him/her, but excludes a TES (ex labour broker) as defined in section 1(1) of the Labour Relations Act 1956 (Act No. 28 of 1956)
Environment	(32-94) means: a) the land, water, and atmosphere of the earth; b) micro-organisms and plant and animal life; and c) any part or combination of (a) and (b) and the interrelationships among and between them, and the physical, chemical, aesthetic, and cultural properties and conditions of the foregoing that influence human health and well-being
Eskom Kusile Power Station Requirements	Eskom Kusile Power Station requirements flowing from directives, policies, standards, procedures, specifications, work instructions, guidelines, or manuals
Fall Protection Plan	(OHS Act) means a documented plan of all risks relating to working from an elevated position, considering the nature of work undertaken, and setting out the procedures and methods to be applied in order to eliminate the risk
Hazard	(OHS Act) means a source of, or exposure to, danger
Hazard Identification	(OHS Act) means the identification and documenting of existing or expected hazards to the health and safety of persons, which are normally associated with the type of construction work being executed or to be executed
Occupational Health and Safety File	(OHS Act) means a file or other record in permanent form, containing the information required in relation to the contract.
Health and Safety Plan	(OHS Act) means a document plan that addresses hazards identified and includes safe work procedures to mitigate, reduce, or control hazards identified
Occupational Health and Safety Specification	(OHS Act) means a document specification of all health and safety requirements pertaining to associated to a contract, so as to ensure the health and safety of persons.
Occupational Health and Safety Requirements	means comprehensive health and safety requirements for a contract, project, site, and scope of work. This specification is intended to ensure the health and safety of persons, both workers and the public, and the duty of care to the environment. The health and safety requirements must be specific to each contract, project, site, and scope of work

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

Definition	Explanation
Lifesaving Rules	(240-62196227) a rule that, if not adhered to, has the potential to cause serious harm to people
Medical Certificate of Fitness	(OHS Act) means a certificate valid for one year, issued by an occupational health practitioner, issued in terms of the regulations, whom shall be registered with the Health Professions Council of South Africa
Medical Surveillance	(OHS Act) means a planned programme or periodic examination (which may include clinical examinations, biological monitoring, or medical tests) of employees by an occupational health practitioner or, in prescribed cases, by an occupational medicine practitioner
Method Statement	(OHS Act) means a written document detailing the key activities to be performed in order to reduce, as reasonably as practicable, the hazards identified in any risk assessment
Organisation	may be defined as a group of individuals (large of small) that is cooperating under the direction of executive leadership in accomplishment of certain common objects
Pre-job Meetings	(34-227) means a meeting that is held prior to the commencement of the day's work and that is attended by all the relevant employees associated with the work task
Main Contractor	(In the text of this document) Means an employer, as defined in section 1 of the OHS Act, who intends to tender for or has signed a contract with Eskom Kusile Power Station for services rendered.
Provincial Director	(OHS Act) means the provincial director as defined in Regulation 1 of the General Administrative Regulations under the Act
Responsible Manager	Is a Manager of a department, section or operating/business unit who has been appointed as part of the Eskom Kusile Power Station delegation of authority process with the aim to assist the applicable 16(2) assigned person in executing his/her duties in terms of the Occupational Health and Safety Act
Risk Assessment	(OHS Act) means a programme to determine any risk associated with any hazard at a construction site in order to identify the steps needed to be taken to remove, reduce, or control such hazard.
Site	(34-228) means an Eskom Kusile Power Station department, unit, complex, building, specific project, work site, or the site where agents, clients, Main contractors, contractors, suppliers, vendors, and service providers provide a service to Eskom Kusile Power Station , directly or indirectly
Task	(34-227) a segment of work that requires a set of specific and distinct actions for its completion

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

Definition	Explanation
Toolbox Talks	(34-227) where the team leader, after conducting pre-task planning, shares all the tasks at hand and discusses task allocation, the identified risks, and the control measures with all his/her team members on site before commencing a specific task and documenting the agreed strategy. (This shall be done to ensure common understanding of the tasks, risks, and control measures required.)
The Act	(OHS Act) means the Occupational Health and Safety Act No. 85 of 1993, as amended, and the Regulations thereto
Visitor	any person visiting a workplace with the knowledge of, or under the supervision of, an employer.

2.4 Abbreviations

Abbreviation	Description
CE	Chief Executive
COID Act	Compensation for Occupational Injuries and Diseases Act
DMR	Driven Machinery Regulations
DEL	Department of Employment and Labour (Inspection and Enforcement services – Provincial office)
EP	Emergency Preparedness
EAP	Employee Assistance Program
ERfW	Environmental Regulations for Workplaces
GAR	General Administrative Regulations
GHS	Global Harmonized System
GSR	General Safety Regulations
HCA	Hazardous Chemical Agents
LDV	Light Delivery Vehicle
PJFF	Pulse Jet Fabric Filter
SDS	Safety Data Sheets
OHS Act	Occupational Health and Safety Act and Regulations, 85 of 1993
O&M	Operating and Maintenance
LoG	(COID) Letter of Good Standing
SABS	South African Bureau Standard
SANS	South African National Standard

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

2.5 Related/Supporting Documents

Section 37(2) of the OHS Act requires Eskom Kusile Power Station to sign an agreement and include it in the OHS file for evaluation prior to the start of work. OHS department will issue the 37(2) agreement to the project manager/end user who will facilitate the signing of the document by Eskom Kusile Power Station and contractor representatives.

3. Document Content

3.1 Scope Of Work

3.2 Employer's Requirements for the Service

3.2.1 Applicable Scope of Work

Mechanical maintenance on the conveyor belts plants, including inspection, assessment, and repair in line with the original installed specifications.
All the maintenance activities shall be executed according to the maintenance strategy of conveyor plants in Kusile Power Station. The scope includes, but is not limited to, the following equipment: Conveyor belting system and the mechanical components (Pulleys, Magnets, Idlers, moving heads and etc) Drive system, Take-up system, moving head, including winches, Belt cleaners (i.e., scrapers and belt washing systems) Transfer chute

The scope of work is detailed on the NEC Contract

A copy of the scope of work must be retained by the contractor.
Note: The contractor who will be awarded this contract will be known as the **"Main contractor"** and any contractor appointed by the Main contractor will be known as the **"Appointed contractor"**

3.3 Legal Compliance

3.3.1 Section 37(2) (Legal) Agreement

A section 37(2) agreement must be signed between Eskom Kusile Power Station and the main contractor at the time of submitting the safety file. The main contractor must ensure that a section 37(2) agreement is compiled between the main contractor and all their appointed contractors for the contract. The original copy of the section 37(2) agreement must be retained by the contractor, and a copy must be retained by the responsible project manager/end user. A copy of all the agreements must form part of the respective contractor's OHS file.

3.3.2 Hazardous Work by Children (Child Labour)

The constitution of the Republic of South Africa, in the "Bill of Rights", is clear on the rights of children, especially when it comes to:

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

1. being protected from exploitative labour practices.

2. not be required or permitted to perform work or provide services that

3. are inappropriate for a person of that child's age; or

4. This places at risk the child's well-being, education, physical or mental health, or spiritual, moral, or social development and the Basic Conditions of Employment Act, Chapter six, Section 43, "Prohibition of employment of children."

Before resorting to the use of child labour, due consideration must be given to the child's constitutional rights. Where work is being performed which is not prohibited in terms of the constitution, then such work must be conducted in terms of the OHS Act "Regulations on Hazardous Work by Children in South Africa" with emphasis on paragraph 2: Purpose and Interpretation. Eskom Kusile Power Station does not condone the use of child labour and, therefore, all effort must be exercised, and child labour should not be used.

3.3.3 OHS Act

The main contractor and appointed contractors shall have an up-to-date copy of the OHS Act and regulations which will be available to all employees.

3.3.4 Legislative Compliance

All contractors will comply with all the legislation pertaining to this contract being:
The Main contractor and all appointed contractors will comply with all the legislation pertaining to this project being:

1. The Constitution of the Republic of South Africa (particularly Section 24 of the Bill of Rights).
2. Occupational Health and Safety Act 1993 (Act 85 of 1993) and its Regulations.
3. National Environmental Management Act 1998 (Act 107 of 1998).
4. Environment Conservation Act 1989 (Act 73 of 1989).
5. National Water Act 1998 (Act 36 of 1998).
6. Civil and Building Work Act.
7. National Road Traffic Act 93 of 1996.
8. Compensation for Occupational Injures and Diseases Act.
9. SANS Standards – Contractor shall use the relative standards applicable to the project.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

3.4 Eskom Kusile Power Station Requirements

All contractors shall, before commencement of the project ensure that all their employees are familiar with the relevant Eskom Kusile Power Station OHS documentation that is applicable to contract services.

3.5 SHEQ Policy

A SHEQ policy is a statement of intent and a commitment by the organization's CE and senior management in relation to the relevant OHS roles and responsibilities, the achievement of their strategic objectives, and values of integrity, customer satisfaction, excellence, and innovation. The main contractor and all appointed contractors, if not already in place, will be required to compile an organisational SHEQ policy in line with their OHS responsibilities. The policy must be signed by the organisation's CE or the appointed assistant to the CE, OHS Act Section 16(2). The policy must be displayed in a prominent place within the workplace. A copy of the policy must be filed in the contractor's OHS files and attached as an annexure to the OHS Plan. OHS Policy to comply with the requirements of OHS Act Section 7 and ISO 45001:2018, Clause 5.2.

3.6 COID

The Main contractor and all his/her appointed contractors shall be registered with an appropriate employment compensation commissioner and have available a valid letter of good standing (LoG) from such commissioner. The obligation lies with the contractors to ensure that the LoG remain valid throughout the contract period. A copy of the LoG must be filed in the contractor OHS files.

3.7 Costing For OHS Within the Project

The costing for OHS must be itemised based on the overall scope of the project (i.e.) Trainings on safety, provision of PPE, safety equipment purchases, Medical Surveillance, Occupational Hygiene Assessment, Health Risk Assessment, ensure all the costing is included on the BOQ.

3.8 Statutory Appointments

The Main contractor and all appointed contractors must appoint competent workers who will comply with the OHS Act for the duration of the contract. Before requiring appointees to accept an appointment, the employer must ensure that they have received appropriate training and/or information about their responsibilities. The relevant statutory appointments must be made in compliance with the OHS Act's criteria, which include appointing a qualified individual to the appropriate roles. The following should be included in the statutory appointments, but not limited to:

1. OHS Act General Administrative Regulation 9(2) – Incident Investigator To be trained on Incident Investigator
2. OHS Act General Safety Regulations 3(4) – First Aider/s

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

3. 16.2 Appointee (To be trained on Legal Liability and OHS Act Training
4. HS Act Section 19 (3) - Health and Safety Committee Member
5. OHS Act, Section 17 – Health and Safety Representative.
6. OHS Act General Machinery Regulation 2(1) – Supervision of Machinery
7. OHS Act: Pressure Equipment Regulations 11 & 12 Portable Gas Container Inspector
8. OHS Act: General Safety Regulation 8 (a) Competent person for stacking & storing

3.8.1 Non Statutory Appointments

1. Eskom Kusile Power Station Site Supervisor (to be trained on OHS Act and Legal Liability, HIRA, Supervisory Safety and Planned Job observation
2. Risk Assessor (to be trained on HIRA
3. Safety Officer
4. Working at Heights planner
5. Hazardous Chemical Agent Co-coordinator
6. Fall protection planner.
7. Emergency Planning Co-coordinator.
8. Chairperson of Health and Safety Committee
9. Competent person for inspection of fire equipment
10. Vehicle & mobile plants inspector

3.9 Eskom Kusile Power Station Life-Saving Rules

1. Eskom Kusile Power Station places a high value on health and safety and urges every organization that undertakes work for Eskom Kusile Power Station to do the same.
2. Eskom Kusile Power Station has developed five life-saving guidelines that will apply to all Eskom Kusile Power Station employees, agents, consultants, and contractors. Any Eskom Kusile Power Station employee or employee of a Main Contractor or appointed contractor who fails to follow these rules would be deemed a serious violation. These rules are in place to protect any employee, labour broker, or contractor working from significant injury or death.
3. If any contractual work (including delivery of any product) is to be undertaken on Eskom Kusile Power Station premises, the rules shall be obeyed by any contractor and their employees.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

The rules are:

RULE	DESCRIPTION OF RULE
Rule 1	**OPEN, ISOLATE, TEST, EARTH, BOND, AND/OR INSULATE BEFORE TOUCH** (That is plant, any plant operating above 1000 V)
Rule 2	**HOOK UP AT HEIGHTS** Working at height is defined as any work performed above a stable work surface or where a person puts himself/herself in a position where he/she exposes himself/herself to a fall from or into.
Rule 3	**BUCKLE UP** No person may drive any vehicle on Eskom Kusile Power Station business and/or on Eskom Kusile Power Station premises: Unless the driver and all passengers are wearing seat belts.
Rule 4	**BE SOBER** No person is allowed to be under the influence of intoxicating liquor or drugs while on duty
Rule 5	**PERMIT TO WORK** Where an authorisation limitation exists, no person shall work without the required permit to work.
Rule 6	**Ensure Safe Live Working**
Rule 7	**NO REVERSING WITHOUT A SPOTTER OR FLAGMAN** Ensure that construction vehicles are only reversed when a spotter or flagman is in place

Eskom Kusile Power Station will take a zero-tolerance approach to these policies.

Noncompliance to Life-saving rules is regarded serious misconduct and will result in serious disciplinary action, which may include dismissal.

This is to ensure that everyone who works on or visits an Eskom Kusile Power Station facility returns home to their families safely.

3.10 Substance Abuse

1. Alcohol and substance abuse are serious threats to any business, especially when it comes to workplace accidents and car driving. As a result, Eskom Kusile Power Station has the right to take reasonable procedures to identify and prohibit drunk people from entering the company.
2. General Safety Regulation 2A specifies the legal position on intoxication.
3. The allowable alcohol and drug level is 0%.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

4. All contractors must follow Eskom Kusile Power Station 's procedure 32-37 ("Substance Abuse Procedure"), considering that this is an Eskom Kusile Power Station Life-saving Rule number 4: (BE SOBER"), and anyone entering the Kusile site will be subjected to ad hoc alcohol testing
5. Contractors are invited to develop their own manual and test their own employees for alcohol on a regular basis.
6. Test results must be marked "Confidential" and kept in the employee's personal file.
7. Eskom Kusile Power Station 's life-saving rules must be included in the induction process.
8. All employees involved in the scope of work must sign the Life-saving rule pledge before commencement of work.

3.11 Contractor Organisational Structure

3.11.1 Main Contractor Organogram

The Main contractor must provide an organisational organogram on the company's letter head related to this contract, depicting all the levels of responsibility from the CE down to the supervisors responsible for the contract. List the relevant positions held, names of appointees, legal appointments and the Organogram must be signed off by the company's 16(1) or 16 (2).

The Main contractor must ensure that all appointed contractors comply with this requirement. The Main contractor is responsible for keeping copies of all the organograms' as well as submitting them with the OHS plan. All organograms shall be updated timeously when appointments are changed.
This diagram must be kept up to date and filed in the project OHS files.

3.11.2 Appointed Contractor/s Organogram

1. Appointed contractors are required to compile their company organogram for the project on the company's letterhead, listing the reporting structure from their CE down to their project supervisors. The diagram must list the names, positions held, any appointments made and must be signed off by the company's 16(1) or 16 (2).
2. This diagram must be kept up to date, a copy of which must be given to the Main contractor and a copy filed in the relevant project OHS files.
3. This diagram must be kept up to date and filed in the project OHS files.

3.12 Roles and Responsibilities

Commitment

Visible commitment is essential to providing a safe work environment. Managers, supervisors and employees at all levels must demonstrate their commitment by being proactively involved in the day to day operations, in particular the Occupational Health and Safety aspects of any project / contract. Legislation requires that each employee must take reasonable care of themselves and their fellow workers, from management level down to the lowest employee level.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

3.12.1 Main Contractors and Appointed Contractors

Note 1: Most of the roles and responsibilities listed apply to both Main contractors and any appointed contractors. Where some of the listed do not apply to both, then the specific responsibilities will be listed and titled. The contractors shall:

1. Carry out all duties as listed in section 8, 9 and 10, the various other regulations that form part of the OHS Act.
2. Carry accountability and responsibility for the safety and health of their employees and their appointed contractors within their working area, as contemplated by section 37(2) of the OHS Act;
3. Shall keep a record of all employees including the appointed contractor employees, including date of induction, relevant skills and licenses and be able to produce this list at the request of the Eskom Kusile Power Station Project Manager.
4. Ensure that all their appointees are made aware of their accountabilities and responsibilities in terms of their appointment and that they advise and assist these appointees in the execution of their duties.
5. Ensure that the minimum legislative, regulatory and Eskom Kusile Power Station OHS requirements are complied with on all work sites.
6. Give the Eskom Kusile Power Station project managers and line managers / responsible managers their full participation and cooperation.
7. Compile a OHS (Occupational health and safety) file where all relevant health and safety records must be kept for each work site.
8. The Main contractor must provide the project manager with the Compensation Commissioner's valid letter of good standing before the commencement of work and any future renewal letters obtained during the contract for record-keeping purposes. The letter of good standing shall reflect the name of the contractor's company. Similarly, the Main contractor must provide the Eskom Kusile Power Station project manager with all the valid letters of good standing from their appointed contractors.
9. Contractors must provide the Main contractor with a certified copy of the Compensation Commissioner's valid letter of good standing before the commencement of work and any future renewal letters obtained during the contract for record-keeping purposes. The letter of good standing shall reflect the name of the contractor's company.
10. Appoint competent staff to perform the project work and ensure that all employees are trained in the health and safety aspects relating to such work and that the employees understand the hazards associated with all other work being carried out on the project.
11. Ensure that all employees are conversant with all relevant work procedures and that they adhere to such procedures. Similarly (without removing the appointed contractors' responsibilities), ensure that their appointed contractors and their employees are conversant with all relevant work procedures and that they adhere to such procedures.
12. Co-ordinate the activities of all the appointed contractors in the interests of safety and health;

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

13. Ensure that their contractors (whom they intend appointing) have made detailed provision for the cost of safety and health measures throughout the project.
14. Stop his /her employees and any appointed contractors if such work poses a threat to the health and safety of persons or a risk of degradation to the environment.
15. Take reasonable steps to ensure cooperation between all their appointed contractors.
16. Ensure that Eskom Kusile Power Station OHS requirements are communicated to the appointed contractors, evaluate, and assess the appointed contractors OHS files. Only appoint contractors who are competent to do work, have satisfied the OHS compliance requirements and satisfied that the contractor has the necessary competencies and resources to perform the work safely. the appointed subcontractor Safety file shall be submitted to Kusile power station together with the main contractor evaluation report for verification and thereafter issue the authorization Letter .
17. Appoint full-time competent employees in writing to supervise the performance of all specified work throughout the contract period.
18. Ensure that the supervisor or manager do not supervise work on any site other than the site for which such supervisor has been appointed for.
19. Not victimise or dismiss employees, by virtue of the employee's divulging health and safety information or suspecting such information has been divulged, in the interests of health and safety requirements.
20. Follow a process of disciplinary action if any of their employees or their appointed contractor employees have transgressed any of the requirements of the health and safety specification, safety and health plans, site rules or any other requirements.
21. Before the commencement of work, review the submitted baseline risk assessments to include site or emerging risks. This should be done by a competent person appointed in writing with a view to identify hazardous and potentially hazardous work operations.
22. Ensure that pre-task risk assessments are conducted and documented daily and prior to the starting of any new task, irrespective of whether it is a repetitive task or not.
23. Must ensure that an organisation medical surveillance programme for the duration of the contract is in place and maintained.
24. Prior to having pre-employment and periodic medicals fitness examinations conducted, person/man job specifications must be compiled and handed to the occupational health practitioner.
25. Issue risk-based personal protective equipment (PPE) as a measure of last resort to their employees, inspect such equipment regularly and ensure recipients of PPE are trained in the proper use, care and where necessary, the maintenance of PPE;

Note: should the Main contractor or his/her appointed contractors entertain visitors on site, they will be held responsible for the provision and wearing PPE.

26. Must have a substance abuse program which must be in line with Eskom Kusile Power Station requirements.
27. Ensure that all incidents are reported and investigated timeously by competent incident investigators as and aligned with 32-95 requirements.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

28. Be involved in all of their appointed contractor's incident investigations.
29. When appointing contractors, advise the project manager in writing timeously and obtain his/her approval prior to them commencing work.

3.12.2 Contractor Site Supervisor

The contractor site supervisor must be trained in the following:

HIRA, Incident investigation training, Supervisory Safety, OHS Act and Legal liability,

Must:

1. Be competent to perform Pressure testing and calibration supervisory tasks
2. Ensure their employees and all appointed contractors comply with the required statutory and Eskom Kusile Power Station project requirements.
3. Inspect all work done by the contractors to ensure adherence to Eskom Kusile Power Station 's standards and specifications
4. Conduct follow-up inspections to ensure findings are closed out and preventative action is in place.
5. Monitor contractors for adhere to statutory requirements and safety standards.
6. Monitor contractors overall OHS performance on site in order to achieve excellent results
7. Discuss all OHS related problems with the relevant contractor management timeously in the first instance and thereafter the Eskom Kusile Power Station project manager in the second instance relating to procedure requirements, non-conformances identified, corrective actions, audits and inspection schedules.
8. Continual liaison between the Main contractor, appointed contractors and employees.
9. Ensures that employees and appointed contractors are aware of latest standards, procedures, work instructions and safety regulations issued by Eskom Kusile Power Station:
10. Conduct site Inspections for compliance to OHS requirements and compiles the relevant inspection reports.
11. Submit the observation reports to the relevant management.
12. Submit the required OHS reports communicated by Eskom Kusile Power Station e.g. manpower numbers, incident statistics report etc
13. Have meaningful participation in the project statutory health and safety committee meetings.
14. Participate in all incident investigations.
15. Participate in the contractor's emergency preparedness planning.
16. Ensure that their own employees and those of any appointed contractor are competent to perform the tasks assigned.
17. Issue site instructions on behalf of the Main contractor where and when the appointed contractors deviate from safety requirements.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

3.12.3 Contractor Health And Safety Officer

Full time Safety Officers are required for this contract.

The contractor health and Safety officer shall meet the following requirements:

National Diploma in Safety Management / Environmental Health , HIRA, Incident investigation training, Legal liability, Training, knowledge and understanding of ISO 4500 Minimum work experience 3yrs,

3.13 Risk Assessment (Refer To 32-520)

It is a legal requirement in terms of Section 8 (2)(d) of the OHS Act for an employer to carry out risk assessments, to establish which risks and hazards are attached to the health and safety of persons due to any work which is performed, any article or substance which is, handled, stored, transported. A risk assessment is defined as an identification of the hazards present in the activity, work, site, and an estimate of the extent of the risks involved, considering whatever precautions are already being taken.

It is essentially a three-stage process:

a) identification of all hazards.

b) evaluation of the risks;

c) Measures to control the risks.

Risk assessments are required to be maintained. This means that significant changes to a process or activity, or any new process or activity should be subjected to a risk assessment and that if new hazards come to light during the work process, then these should also be subjected to risk assessments. Risk assessments for long term processes should be periodically reviewed and updated. Method statements or written safe work procedures are an effective method as information and record of the way jobs / tasks must be performed. Daily or issue based or task specific or on the job risk assessments must be conducted at the place where work is to be performed/ conducted to allow managers and employees to assess any inherent risks that could have been overlooked during the initial risk assessment or any changes that might have occurred in a period of absence. For example if a job / task is extended over a day or halted due to inclement weather.

Guidelines for actual steps involved in a job/task specific risk assessment are:

1. Each activity is listed.
2. Specific hazards are identified and listed against each activity.
3. The magnitude of each risk is rated as Low. Medium or High.
4. All known documentary and supervisory controls are listed. For instance: What safe work procedures exist for ladders.
5. The relevance, effectiveness and sufficiency of these controls are assessed.
6. In the event of insufficient or deficient controls for the particular activity, steps to be taken to rectify this shall be recorded, and safe working procedures drawn up.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

7. Persons responsible for implementing and supervising the task shall be identified, nominated and duly assigned.
8. Persons responsible for monitoring the task and carrying out the planned job observation must be nominated.
9. Completed risk assessment shall be handed to the Eskom Kusile Power Station project manager representative for comment and approval.
10. The relevant section of the risk assessment shall be issued with a Transmittal Note to the Supervisor nominated as the responsible person; and the names of workmen who have received instruction on the work content and the sequence of the activities listed in the risk assessment shall be recorded, and their competence established. This instruction shall be done through an interpreter if required and recorded on the Pre-Job Brief (Daily Safe Task Instructions), with reference to applicable Risk Assessments

3.14 Safe Work Procedures / Method Statements

There must be written safe work procedures for all activities, the safe work procedures must be aligned with the risk assessments. Method statements / written safe work procedure are control measures used to prevent an incident from occurring during the execution of the project. A written safe work procedure/ method statements provide guidance how to execute the task safely. A safe working procedure should be written when: -

a. Designing a new job or task.
b. Changing jobs or task;
c. Introducing new equipment or substances; and

The safe working procedure should identify:

a. The supervisor for the task or job and the employees who will undertake the task;
b. The tasks that are to be undertaken that pose risks;
c. The equipment and substances that are used in these tasks;
d. The control measures that have been built into these tasks;
e. Any training or qualification needed to undertake the task;
f. The personal protective equipment to be worn;
g. Actions to be undertaken to address safety issues that may arise while undertaking the task.

The appointed contractor to submit the Safe work procedure related to the scope of work.

Prior any work execution employee shall be made conversant with the relevant Safe work procedure, during work execution team shall always have the copy of the SWP where the work is done for referencing.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

3.15 Roof Work (Refer To 32- 418)

N/A

3.16 Fire Equipment and Maintenance

1. All firefighting equipment's that have been provided shall:
   a. Be clearly labelled
   b. Conspicuously numbered
   c. Entered in a register
   d. Inspected monthly by a competent person
2. Tested and serviced every 12 months.
3. Results entered in the register and signed by competent person.

3.17 Flammable, Combustible Liquids and Hazardous Chemical Agents

1. Ensure the implementation and compliance to HCA GHS.
2. the contractor shall ensure that an HCA that is used, handled, or stored at the workplace is correctly labelled as per GHS Requirements.
3. GHS compliant safety data sheet must be presented.
4. Ensure that a container labelled for an HCA is used for only
5. the use, handling, or storage of that HCA.
6. as far as is reasonably practicable, ensure that when an HCA is transferred or decanted at the workplace, from its
7. original container into a destination container, the destination container is correctly labelled for that HCA.

Safety Data Sheets (MSDS) for materials in accordance with the requirements of the OH&S Act Regulations for Hazardous Chemical Agents.

1. Purpose for using the hazardous Agent.
2. Proposed arrangements for safe storage.
3. Proposed methods for handling / usage.
4. Proposed method of disposal.
5. Hazard communication / training plan.
6. A copy of the assessment that shall fulfil the requirements of the HCA regulations
7. Details of maintenance of control measures to ensure optimum efficiency

Storage of Hazardous Agents

1. A register of Hazardous Agent and Safety Data Sheets shall be developed, maintained, and kept at the Contractor's Site Office.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

2. Without limiting the Contractor's responsibilities under applicable Legislation, work shall be conducted in such a manner as to ensure that: No substance, which can harm or is likely to harm the environment, is to be allowed to leak, spill or escape from any container or storage area.
3. No oil or other effluent is permitted to escape into the drainage system and / or local storm water system.
4. No oil or other effluent is permitted to escape into the ground and cause soil contamination

3.18 First Aid and Equipment

1. The requirements of the OHS Act GSR 3 must be observed.
2. The competency ought to be in line with latest Department of Employment and Labour requirements (No level 1,2,3 will be accepted but relevant unit standard should be indicated and Competency Certificate should be from Accredited institution. QCTO/SETA accredited and DoEL approved training providers, providing skills programmes/unit standard training will only be accepted, which includes:

   US 120496 – Provide risk-based primary emergency care/first aid in the workplace.

   US 376480 – Provide first aid as an advanced first responder.

3. When appointing employees for work sites, cognisance must be taken into account the type of work performed, the distance teams are working apart and the terrain to be covered if an emergency should arise.
4. A list of emergency numbers must be displayed on the notice boards and made accessible for all employees.
5. Main Contractor must ensure that his /her employees and appointed contractor employees are familiar with the emergency numbers.
6. Contractors shall have one first aid box for the first 5 persons and thereafter one for every 50 or team of workers on site or part thereof, taking into account the type of work performed and the distance between teams.
7. More first aid boxes shall be provided in accordance with the risk assessment. Boxes must be available and accessible for the immediate treatment of injured persons at the workplace.
8. For offices, signs indicating where the first aid box or boxes are kept as well as the name and contact details of the First Aider of such first aid box or boxes shall be erected.
9. The Main Contractor and appointed contractor shall ensure that alternative arrangements be made for incidents occurring after working hours.

3.18.1 Boxes and Equipment

The following is a list of minimum contents of a first aid box:

1. Item 1: Wound cleaner/antiseptic (100ml).
2. Item 2: Swabs for cleaning wounds.
3. Item 3: Cotton wool for padding (100 g).
4. Item 4: Sterile gauze (minimum quantity 10).

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

5. Item 5: 1 Pair of forceps (for splinters).
6. Item 6: 1 Pair of scissors (minimum size 100 mm).
7. Item 7: 1 Set of safety pins.
8. Item 8: 4 Triangular bandages.
9. Item 9: 4 Roller bandages (75 mm X 5 m).
10. Item 10: 4 Roller bandages (100 mm X 5 m).
11. Item 11: 1 Roll of elastic adhesive (25 mm X 3 m).
12. Item 12: 1 Non-allergenic adhesive strip (25 mm X 3 m).
13. Item 13: 1 Packet of adhesive dressing strips (minimum quantity, 10 assorted sizes).
14. Item 14: 4 First aid dressings (75 mm X 100 mm).
15. Item 15: 4 First aid dressings (150 mm x 200 mm).
16. Item 16: 2 Straight splints.
17. Item 17: 2 Pairs large and 2 pairs medium disposable latex gloves.
18. Item 18: 2 CPR mouth pieces or similar devices.

A content check list must be available with all boxes and boxes shall be checked on a regular basis, kept clean and dust free.

An additional first aid provision for eye wash fountain or similar shall be provided as required by general safety regulation 8

3.19 OHS Communication Systems

Main Contractor/s and their appointed contractors must develop a communication strategy outlining how they intend to communicate OHS issues to their staff, the mediums they will employ and how they will measure the effectiveness of their OHS communication. Below is a brief on how communication should take place. Where project meetings are conducted on site, OHS shall be included as a standing agenda point and minutes of these meetings shall be available on site at all times. Minutes of meeting must be compiled and filed in the relevant OHS files. All employees shall have access to these minutes. Attendance register shall be kept for all the health and safety meetings.

3.19.1 Statutory Health and Safety Committees

1. The Main contractor shall establish statutory health and safety committee in terms of Section 19 of the OHS Act. Similarly, appointed contractors shall establish their own statutory health and safety committee.
2. All appointed contractors shall be members of the Main contractor’s safety committee.
3. The Committee shall meet to discuss OHS issues concerning the current work being performed, training, upcoming work and OHS requirements, incidents and lessons learned specific OHS problems, safety performance, action plans and other relevant OHS issues. Listed below is a preferred agenda.
4. OHS representatives for a workplace shall be members of the relevant workplace safety committees (Refer to Section 19 (2) (a) of the OHS Act).

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

5. The number of persons nominated by employer must not be more than the Health and Safety Representatives on that specific statutory health and safety committee. (Refer to Section 19(2)(c) of the OHS Act)
6. A statutory health and safety committee meeting shall be held at least 3 monthly (where medium to high risk work is involved, more frequent if required), and all appointed members of the committee shall attend the meeting.
7. Statutory health and safety committees may make recommendations to the Main contractor and the project manager and the Inspector at DEL.
8. All health and safety committees shall discuss all projects related OHS Act Section 24 and 25 incidents and other notified serious incidents.
9. Health and safety committees shall follow up on incident investigation recommendations and shall keep record of all recommendations made by the committee.
10. Statutory health and safety committees may make recommendations for the revision of current standards, procedures and practices.
11. The Main contractor and appointed contractors shall ensure that statutory and non-statutory health and safety committees carry out their duties.
12. The chairperson of the health and safety committees shall be selected and appointed by the contractor. The appointed chairperson must be competent to chair meetings and be able to make informed decisions.

3.19.2 Non-Statutory Health and Safety Committees

1. Where there are large worksites, then non-statutory sub-committee must be established within that worksite to assist with the communication of health and safety related matters between the statutory health and safety committee and the workplace.
2. The duties and responsibilities of the non- statutory health and safety committees will be the same as the statutory safety committee.

3.19.2.1 Agenda

The following serves as the guideline for the OHS Committee meeting agenda.

1. List of agenda items:
2. Matters arising from previous minutes
3. Matters arising from Contractor’s OHS meetings.
4. Covid-19 compliance
5. Audit results and feedback
6. Review Health and Safety Representative Inspection Reports
7. Review
   a) Incident investigation reports
   b) Non-Conformances

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

c) Announcements (near miss/injury/damage)
d) Follow up on recommendations made by the employer in incident investigation reports

8. Accident Prevention – Safety Promotion

a) Planned Job Observations
b) OHS Training
c) Protective clothing and equipment
d) Incident Announcements / Recall

9. Forthcoming High hazard activities.
10. Non-conformances.
11. Housekeeping.
12. Work permits.
13. Work procedures.
14. Hazardous materials / substances.
15. Fire Prevention
16. Occupational Hygiene Assessments, Health Risks and Actions
17. Security
18. Rules, Instructions
19. Public Safety
20. Environmental Management
21. Emergency Preparedness
22. Statistics report
23. Closure

3.19.2.2 Minutes And Action Items for All Health And Safety Committee Meetings

1. Minutes and record of action items shall be kept of all health and safety committee meetings.
2. Action column with target dates and responsible person shall be clearly visible on the minutes and shall be completed during the meeting.
3. Statutory health and safety committee meeting minutes and record of action items shall be kept for the duration of the project or a minimum period of three years.
4. Non–statutory health and safety committee meeting minutes shall be kept for the duration of the project or a minimum period of 12 months.
5. All other meeting minutes where OHS is on the agenda, shall be kept for a minimum period of 12 months.
6. The original copy of the minutes and record of the action items must be signed by the chairperson.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

7. The relevant project manager and Main contractor shall endorse the relevant minutes with his/her recommendations and return the minutes to the relevant contractors chairperson within 14 calendar days of the meeting.

3.20 Tool Box Talks / Daily Team Talks / Pre Job Meetings

1. A meeting must be held prior to the commencement of the day's work with all relevant personnel associated with the work task in attendance. The job, relevant procedures, associated hazards, safety measures, i.e. the task risk assessments shall be discussed. Each employee who attends the briefing shall sign an attendance list of that pre-job brief form undertaking that they have an understanding of the tasks, risks and control measures required.
2. Where possible, tool box talks can be included in the pre-job brief meetings. If this does not occur, then weekly tool box talks must be conducted. The toolbox talk topics will be based on OHS issues pertaining to the project site. The topic and the contents shall be in writing. Attendance registers with the topic listed shall be kept.

3.21 OHS Training

1. The Main contractor, when making a bid for this project shall provide a breakdown list of the OHS training requirements and the costing of such requirements. Similarly, appointed contractor must provide the same requirements when bidding with the Main contractor.
2. The scope of training includes but is not limited to the type of work being performed and the relevant procedures. Additional to the requirements, will be that the Main contractor and appointed contractors must have the appropriate qualifications, certificates and employees should always be under competent supervision. All]
3. Where legislative and Eskom Kusile Power Station recommended appointments are made, the relevant training shall be given to those appointees prior to the acceptance of those appointments.
4. When there is an amendment to the Acts and/or to the regulations, OHS specification and OHS plan, all affected staff shall undergo the applicable refresher training.
5. Appropriate time must be set aside for training (induction and other) of all employees.
6. Records of all training and qualifications of all contractor employees must be kept on the OHS file.
7. All employees working with Chemicals to be trained on Handling of Hazardous Chemicals,
8. All relevant SDSs for the Hazardous chemicals Agents to be communicated to the employees and including training on in case of emergency situations.
9. All employees to

3.21.1 Main Contractor Induction Training

The contractor is required to make arrangements with the Business Unit for its employees to attend induction in order to be granted permission to access site.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

1. The Main contractor shall ensure that all his / her employees, appointed contractors and their employees have undergone the Eskom Kusile Power Station OHS induction training prior to commencing work on site.
2. Attendance registers must be completed of any induction training given, which must indicate that they have received and understood the induction training.
3. Prior to attending the induction training, all employees must undergo a pre-employment medical examination and found fit for duty. A copy of the certificate of fitness must be kept in the OHS file on site for the duration of the project.
4. All employees and visitors on site shall carry the proof of induction training.
5. It is the contractors responsibility to keep records of induction training.

Visitors To Site Induction

1. Visitors to the site shall be required to undergo and comply with the Eskom Kusile Power Station site-specific safety induction prior to being allowed access to site.
2. All visitors must remain in the care and custody of a person (host) who has been properly inducted. No visitors are permitted to undertake any work onsite, of any nature.
3. Visitors who have completed site induction must be provided with a record of proof of Induction training.

3.22 General Training

The Main contractor will be required to ensure that before an employee commences work on the project/site, the respective supervisor informs the employee of his scope of authority, the hazards associated with work as well as the control measures to be taken. This will include man-job specifications, the discussion of any task procedures or hazardous operational procedures to be performed by the employee. The Main Contractor is to ensure that the supervisor has satisfied himself that the employee understands the hazards associated with the work to be performed by conducting task/job observations.

3.23 Contractor Site Establishment

Contractor to comply with the Facilities Regulations, SANS 10400, and CR 30 (use as guide for non-construction work).

1. Site establishment walkdown shall be conducted prior to commencement of contractor on site, records retained for audit purposes.
2. Actions emanating from the site establishment shall be tracked and closed by the contracts manager
3. Every site shall have a layout plan.
4. Erect a fence/physical demarcation - erect fences or physical demarcation around the allocated site.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

5. Identifying information – put signage with the details of the company and contact number, directions for site visitors and instructions on what personal protective equipment (PPE) must be worn, specific PPE is required.
6. Vegetation management – each contractor shall be responsible for maintaining vegetation in and around its yard to an acceptable standard.
7. Physical structures shall be constructed and approved by the applicable professional and maintained as per the requirements.
8. Access and egress – must be safe and easy to enter or leave the site with sufficient separation between personnel and mobile plant.
9. Layout - separate different activities on site, these could include a lay down yard, workshop, hot works area and car park.
10. Offices and workshops – must be in line with Eskom and legal requirements, this covers but not limited items like illumination, ventilation, lockers, furniture etc
11. Signage – provide adequate signage as per the risk assessment, this includes warning, information, prohibition signs, etc and location of emergency response equipment.
12. Access restrictions – obtain permit to gain entry to the area that require specific permit or approval.
13. Security – ensure that the site is secure, and assets on site are kept safe after hours
14. Amenities – comply with Eskom and legal requirements, this covers but not limited to items like toilets, eating areas, changing areas, drinking water, first aid, COC and emergency response planning.
15. Hazard awareness – identify the hazards and risks on site and apply management controls to minimise risk.
16. Contact lists: These should include frequent suppliers, health and safety representatives and emergency contacts.

3.24 Site Roads

1. When planning, sufficient areas must be allocated for parking of vehicles and mobile equipment's as well as roadways for ease of manoeuvrability of these vehicles.
2. Sufficient width roads to be provided and adequate space is to be allowed for large vehicles traversing the sites.

3.25 Vehicle Management

1. It is the responsibility of the driver to ensure:
   a. Their passengers wear seat belts whilst the vehicle is in motion.
   b. Comply with all traffic road rules, safety, direction and speed signs.
   c. Ensure that vehicle loads are properly secured prior to moving off.
   d. Ensure that vehicles are not overloaded.
2. No persons maybe transported at the back of the bakkie.
3. Drivers are required to conduct the route risk assessment prior to travelling/driving.
4. No drivers or operators may text, talk on cell phones or two-way radios whilst driving.
5. All drivers shall have a valid medical fitness certificate.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

6. The First aid box with valid contents and fire extinguishers must be included in the vehicle, be services annually and inspected monthly. Drivers must be trained on how to use the First aid box and fire extinguishers.
7. Two triangles must be included in the vehicle and the emergency number be displayed at the back of the vehicle.
8. Each Project site that is enclosed by demarcation will have system/ process to manage vehicle access to site.
9. Contractor must maintain their vehicles in a roadworthy condition and a vehicle license must be valid at all times and this is applicable to yellow plant.
10. Drivers of light vehicles must avoid stopping or parking in the vicinity of machines. At least 30 (thirty) meters must be left clear between such a vehicle and such a machine.
11. Contractor vehicles can be subject to inspections by the Client/Agent's representative. Vehicles which are not roadworthy will not be permitted to be used on site.
12. Drivers/operators shall be responsible for the travel-worthiness of all loads conveyed by them. Precautions shall be taken to secure all loads properly. Loads projecting from vehicles shall be securely loaded and in daytime a red flag and during darkness a red light or red reflective material shall be attached to the extreme end of such projecting materials.
13. The vehicle inspection checklist must include but not limited to:
    a) Reverse alarm / beeper
    b) Yellow reflective tape
    c) Mud flaps
    d) Fire Extinguisher
    e) 2 Triangles
    f) First Aid Box
    g) Safety belts for every seat
    h) No fold-up or jockey seat
    i) Tyres
    j) License disc
    k) Yellow reflective tape that must be fitted at a height of between 250mm and 1.5 metres
    l) Speed warning sigh (100km/h) at the back of the minibus
    m) Driver has a Public Driving Permit

3.26 Housekeeping and Order

1. All contractors shall maintain a high standard of housekeeping within their sites and vehicles for the duration of the project/contract.
2. Prompt disposal of waste materials, scrap and rubbish is essential and be stored temporarily in a designated waste area, awaiting disposal.
3. Materials/objects shall not be left unsecured in elevated areas – falling objects may cause serious injuries/fatalities.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

4. Nails protruding through timber shall be bent over or removed so as not to cause injury.
5. All packaging material including boxes, pallets, crates, etc. to be removed from the work area immediately.
6. On completion of his / her work, the contractor is responsible for clearing his / her work area of all materials, scrap, temporary buildings and building bases to the satisfaction of the client/agent.
7. In cases where an inadequate standard of housekeeping has developed, compromising safety and cleanliness, anyone has the responsibility to bring it to the attention of the Main contractor in the first instance and the Eskom Kusile Power Station project/contract manager in the second instance.
8. The Eskom Kusile Power Station project/contract manager has the right to instruct the Main contractor and appointed contractors to cease work until the area has been tidied up and made safe. Neither additional costs nor extension of time to the contract shall be allowed as a result of such a stoppage. Failure to comply with this requirement will result into site cleaning by another cleaning contractor company at the cost of the Main contractor.
9. The Main contractor shall carry out regular safety/housekeeping inspections daily to ensure maintenance of satisfactory standards. The Main contractor shall document the results of each inspection and shall maintain records for viewing.

3.27 Stacking and Storage

1. The competent personnel must be appointed in writing to manage and supervise all stacking and storage on site.
2. Before stacking any material, the contractors or their employees must consult the contract manager for authorisation to use such an area for stacking purposes. This is to prevent haphazard arrangements.
3. Adequate care must be taken by the contractor to ensure that storage and stacking is carried out correctly and safely.
4. Correct shelve stacking must be carried out, heavy and bulky on the bottom, light and small on top.

3.28 Workplace Signage and Colour Coding

1. Symbolic safety signage shall be displayed where it is required by legislation.
2. All symbolic safety signage shall conform to the requirements of SANS standard 1186.
3. Signs shall be positioned to be seen from most positions within the work sites / areas.
4. All signage must be clear at all times and be replaced timeously when worn out.
5. Contractors establishing sites must erect a company sign at their site offices to reflect the name and contact details of the: contractor site/responsible manager; supervisors; Health and Safety Manager/Practitioner; First Aider; Health and Safety Representative and Evacuation warden.
6. The location of every first aid box; fire extinguisher and emergency exit is to be clearly indicated by means of a sign.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

7. When using, an explosive power tool the appropriate signage shall be erected, warning people of its use.
8. Contractors shall provide signage where work is conducted and where unauthorised entry is prohibited and/or where alerting and cautioning passers-by to be aware of potential dangers.
9. The meanings of the appropriate symbolic signage must be discussed during induction training and toolbox talks.
10. Where possible, within workshops, work areas and established premises, the appropriate sign indicating the meaning of symbolic safety signs must be displayed.

3.29 Tools and Equipment

1. Contractors shall ensure that all tools and equipment are identified, safe to be used and is maintained in a good condition.
2. Contractors shall ensure that all tools and equipment are listed on an inventory list, be regularly inspected at least monthly or as required by legislation and risk assessments. The equipment should be numbered or tagged so that it can be properly monitored and inspected.
3. Where applicable, tools and equipment must have the necessary approved test or calibration documentation prior to being brought onto the project and the records shall form part of the OHS plan. Maintenance calibration shall be undertaken in terms of the manufacturer's requirements.
4. All fuel driven equipment must be properly maintained in accordance with the manufacturer's recommendations and legal requirements.
5. Eskom Kusile Power Station reserves the right to inspect tools or items of equipment brought to site by contractors for use on this project.
6. Should Eskom Kusile Power Station personnel find any item that is inadequate, faulty, unsafe or in any other way unsuitable for the safe and satisfactory execution of the work for which it is intended, the Eskom Kusile Power Station personnel shall advise the contractor in writing and the contractor shall forthwith remove the item from site and replace it with a safe and adequate substitute.

Note: In such cases, the contractor shall not be entitled to extra payments or extensions of time in respect of delay caused by Eskom Kusile Power Station 's instructions.

7. Where defective tools and equipment's are identified, such tools and equipment shall be removed out of site immediately, locked away to prevent further use until such time as the tool or piece of equipment has been repaired.
8. Contractors shall ensure that the appropriate records are kept for all tools and equipment used on the project. Such tools and equipment's shall be subjected to regular inspections.

3.29.1 Hand Tools

1. All hand tools (hammers, chisels, spanners, etc.) must be recorded on a register and inspected by the construction supervisor on a monthly basis as well as by users prior to use.
2. Under no circumstance will the contractors be allowed to use their equipment's with mushroom heads, to be removed at the end or beginning of shift prior to use.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

3. Tools with sharp points in toolboxes must be protected with a cover.
4. All files and similar tools must be fitted with handles.
5. No make shift tools are permissible on the project.

3.30 Ladders

1. Ladders used shall conform to the requirements of GSR 13A and used in terms of GSR 6.
2. The appropriate head protection, with chin strap shall be worn by employees working from a ladder or with climbing irons.
3. The ladder wheels, brakes and platform must be in good condition.
4. All metal parts to be in good condition, no cracks.
5. The appropriate head protection, with chin strap shall be worn by employees working from a ladder or with climbing irons.
6. Non-slip devices must be in good condition and no paint to be on wooden ladders
7. Climbing irons are permitted to be used in place of ladders on condition that the requirements of GSR 6 are not compromised and from an electrical point of view not damage any cabling. The working at heights risk assessment must indicate the use of climbing irons.
8. Employees using climbing irons shall be suitably trained in the use, care and maintenance of such climbing irons.
9. When using climbing irons, the appropriate rope grab fall prevention system shall be used.
10. The correct fall protection equipment shall be worn and used whilst climbing up, working from and climbing down ladders.
11. The appropriate head protection, with chin strap shall be worn by employees working from a ladder (risk based) or with climbing irons.
12. A detailed inspection of all ladders shall be conducted monthly by a competent person and every time prior to climbing by employees using such ladders. The inspection check lists must be filed in the site OHS files

3.31 Scaffolding

1. Scaffolding use shall conform to the requirements of Eskom Kusile Power Station procedure 32-418 and used in terms of GSR 6.
2. The requirements for using a scaffold platform shall be determined by the work at heights risk assessment.
3. All scaffolding that will be used shall conform to the SANS standard 10085.
4. Scaffolding shall be erected and inspected by the competent personnel.
5. The appropriate training for scaffold users shall be conducted prior to climbing on to the scaffold.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

6. The correct fall protection equipment shall be worn and used whilst climbing up, working from and climbing down the scaffolds as the risk assessment.
7. A detailed inspection of all scaffolding shall be conducted at suitable intervals not exceeding seven days by a competent person and visual inspection shall be done every time prior to climbing by employees using such scaffolding. The inspection check lists must be filed in the site OHS files.
8. Visual inspections must always be carried out prior to every use.

3.32 Auditing

3.32.1 Approval and Compliance of Main Contractor OHS Plan

The Contractor's OHS Plan will be audited against compliance checklist to verify compliance to the requirements of these specification. Once there is compliance only then will the Main contractors OHS plan be approved by the project manager or an appointed Eskom Kusile Power Station contract custodian. The implementation of the OHS Plan will be assessed / audited by Eskom Kusile Power Station personnel on a Quarterly basis. This will include physical conditions evaluation.

3.32.2 Eskom Kusile Power Station OHS Audits

Eskom Kusile Power Station will evaluate the appointed contractor OHS performance on a Quarterly basis against the legal, Eskom Kusile Power Station requirements, OHS specification and the contractor OHS plans.

Note: Eskom Kusile power station reserves the right to conduct unannounced audits on contractors

The contractor will be Audited on a Quarterly basis by Eskom Kusile Power Station on the Main contractor and/or appointed contractors. These audits shall be attended by the contractor's site manager or his representative.

If there are any findings / non-compliance identified as serious in these audits, an activity will be stopped for that specific Main Contractor and appointed contractor. Refer to section on "Work Stoppage" in this OHS Specification.

3.33 Smoking

The national smoking policy must be observed, and smoking is permitted in designated areas only (Eskom Smoking Procedure 32-36)

3.34 Cellular Phones

The National Road Traffic Act requirements regarding the use of cellular phones must be observed, when driving and or operating mobile equipment and or machinery. The personal use of cell phones in the plant is prohibited unless it is an emergency or for work purpose. The use of cell phone camera in the plant must be in line with the national key point Act and the Plant safety regulation.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

3.35 Occupational Health, Hygiene and Rehabilitation

All contractors are required to develop an Occupational Health, Hygiene and Rehabilitation program. The program is intended to ensure that the risks to health are identified and controlled.

All contractors are required to develop an Occupational Health, Hygiene and Rehabilitation program. The program is intended to ensure that the risks to health are identified and controlled.
The contractor must provide training and information regarding the HCA's being transported.
Main contractor/appointed contractor must conduct or develop:
The following records must be available for audits:

1. Health Risk assessment report identifying hazards and risks that the employees are exposed to.
2. Hygiene management Program for appropriate control of exposures.
3. Occupational Hygiene monitoring.
4. Preventive actions (action plan feedback)
5. Exposure survey results.
6. Pre-existing medical conditions and restrictions must be declared with Eskom medical centre for management and accommodation of employees.
7. Complaints records
8. Communication records
9. Reports on control of non-conformance and corrective action
10. Records for training and awareness's
11. PPE records (i.e., dust masks, ear plugs

3.35.1 Medical Assessments

Note: Eskom Kusile Power Station will only accept medical surveillances conducted by an Occupational Health Practitioner who holds a qualification in occupational health.

1. Main contractors must ensure that their employees and their appointed contractor employees have a medical surveillance program whereby their employees undergo entry, periodic and exit medical fitness examinations.
2. The health risk assessment must be used to compile the man job specification and address the hazards that the employees will be exposed to.
3. For the appropriate medical examinations to be conducted, each employee must have a man job specification, which must indicate the description of work, list of hazards and potential occupational exposure limits, physical hazards and required physical attributes.
4. Medical fitness certificates shall be renewed annually for employees who are working on site. This shall be maintained until completion of the contract.
5. The Main Contractor must ensure that his / her employees and appointed contractor employees have undergone pre-entry medical examination before starting work on the contract.
6. The Main contractor shall provide a documented process for managing those employees who are issued with a conditional certificate of fitness.
7. The contractor shall include in the OHS file the record of the employees exit medical fitness certificates as and when their employees leave the company.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

3.35.2 Occupational Hygiene Hazards Identification and Risk Assessment Report (HIRA)

1. The main contractor must ensure that a HIRA is conducted for their employees by an AIA or a competent person to identify the health hazards inherent to specific job tasks and develop actions and recommendations to control health risks presented by hazards identified during this assessment.
2. The HIRA should evaluate health hazards presented by physical stressors such as illumination, noise, ventilation, heat stress, cold stress, vibration and radiation (ionising and non-ionising), ergonomical hazards, chemical agents, hazardous biological agents and psychological stress factors.
3. The HIRA should be conducted before commencement of any work activities and should be repeated if new processes (tasks) are introduced, or if existing processes or tasks are changed or modified. If unchanged, the assessment should in any event be repeated in 24 months

3.35.3 Occupational Hygiene Monitoring

Noise

1. Regulation 7 of the Noise Induced Hearing Loss Regulations, OHSAct (85 of 1993) requires that noise monitoring shall be carried out at the workplace, therefore, the main contractor must ensure that they conduct personal noise monitoring for their employees. Noise surveys must be conducted by an AIA and in accordance with national and / or international methods to evaluate noise rating levels at the workplace.
2. The measurement programme must be in accordance with the requirements of Chapter 3 (sampling of maximum risk employee) and 4 of the Occupational Exposure Sampling Strategy Manual (OESSM), published by the NIOSH, Publication No. 77-173 of 1977, United States of America: Department of Health, Education and Welfare.
3. The survey should be conducted during commencement of work activities to serve as a baseline and thereafter repeated if any of the processes, equipment or the layout of the work areas changes, or if either the controls or assessment are no longer considered to be sufficient. If everything remains the same, the survey should be repeated in 24 months.

Hazardous Chemical Agents (Fly Ash, Respirable Dust and Respirable Crystalline Silica)

1. Regulation 6 of the Regulations for Hazardous Chemical Agents, 2021, OHSAct (85 of 1993) requires that air monitoring and the evaluation of employee exposure to hazardous chemical agents shall be carried out at the workplace, therefore, the main contractor must ensure that they conduct air monitoring for their employees. Air monitoring must be conducted by an AIA and in

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

accordance with national and / or international methods to evaluate employee exposure at the workplace.
2. The measurement programme must be in accordance with the requirements of Chapter 3 (sampling of maximum risk employee) and 4 of the Occupational Exposure Sampling Strategy Manual (OESSM), published by the NIOSH, Publication No. 77-173 of 1977, United States of America: Department of Health, Education and Welfare.
3. The survey should be conducted during commencement of work activities to serve as a baseline and thereafter repeated if any of the processes, equipment or the layout of the work areas changes, or if either the controls or assessment are no longer considered to be sufficient. If everything remains the same, the survey should be repeated in 24 months.
4. The results of the respirable silica dust survey must be submitted to the Department of Employment and Labour in a prescribed format on a bi-annual basis.

3.35.4 Information and Training

The main contractors must ensure that it provides its employees with information and training with regards to:

1. The content and scope of the Occupational Health and Safety Act (82 0f 1993).
2. Potential sources of exposure to health hazards.
3. Potential risks to health and safety caused by exposure to health hazards.
4. Measure taken by Eskom and main contractor to protect employees against detrimental effects of exposure to health hazards.
5. Precautions to be taken by employees to protect themselves against health and risks associated with exposure to health risk, including wearing of personal protective equipment.
6. The necessity, correct use, maintenance and limitations of personal protective equipment, facilities, and engineering controls provided.
7. Assessment of exposure, the purpose of occupational hygiene monitoring and necessity for medical surveillance and long0term benefits and limitations of undergoing such medical surveillance.
8. Procedures for reporting, correcting, and replacing defective personal protective equipment and engineering controls

3.36 Roles and Responsibilities

All contractors are required to list employee’s roles and responsibilities pertaining to the contract.

3.37 Working At Heights

3.37.1 General Requirements

Wherever reasonably practicable, preference is given to the performance of work at ground level as opposed to the elevated position. Where work in an elevated position is necessary, preference is given to fall prevention measures such as, but not limited to, effective barricading and the use of work platforms. Persons may only work from a fall risk position if a site-specific fall protection plan developed by the appointed competent person (as per 32-418 procedure) is in place and correctly implemented and consists of the following:

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

1. All appointments for the fall protection plan developer and implementer are in place.
2. Baseline risk assessment, which is specific and incorporates the working at height risk assessment, as well as the site-specific risk assessment, has been completed for the work to be conducted.
3. Safe working procedure/task analysis and work instructions, approved by a competent person, are in place.
4. A fall rescue plan, along with necessary equipment's and trained rescuers, are in place. Unit standard for Fall rescue plan required is **229995**
5. Appropriate training for working at height unit standard **229998** to be done to all employee working at heights Appropriate height safety equipment and personal protective equipment have been issued to the individual. Duration for **229998 shall be 3 working days.**
6. Appropriate height safety equipment and personal protective equipment have been issued to the individual.
7. There are equipment inspection procedures and up-to-date inspection records.
8. Individuals are medically fit to work at height, and records of this are kept.
9. A site-specific risk assessment is performed.

While work is in progress, adequate warning signs and/or barricades shall be used in all areas where there is a risk of persons being injured by materials or equipment falling from the work area. Barricades should be continuous and easily visible.

A drop zone shall be established with appropriate warning signs and barricading, warning personnel below of workers above and potential falling objects.

Every employer shall ensure that work at height is:

1. Properly planned;
2. Appropriately supervised; and
3. Carried out in a manner that is, as far as is reasonably practicable, safe and that its planning includes the selection of work equipment.
4. For Rope access work that it is carried out in a manner that is, as far as is reasonably practicable, safe and that its design, selection and use of the equipment and anchors complies with safety standards and ensure that the Rope access operators are competent and licenced.

3.38 Personal Protective Equipment Requirements

1. The Main contractor must provide a detailed programme that includes the issuing, maintenance, and replacement of PPE for all his employees and appointed contractors on site.
2. All contractors shall comply with the requirements of GSR 2 of the OHS Act and
3. PPE Specification Standard 240-44175132.
4. The risk based PPE matrix must be compiled detailing the types of PPE that is required to be issued to employees performing the respective tasks.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

5. If there are exceptional circumstances in which certain activities necessitate the use of additional PPE, a risk assessment must be done, in which such PPE requirements will be determined and issued.
6. All contractors shall ensure that their visitors wear and use the correct PPE whilst on worksites.
7. Where PPE is required and visitors are not in possession of, then it is the individual contractor's responsibility to provide the PPE.
8. All PPE purchased and used by all contractor employees including visitors must comply with the relevant SANS standards.
9. Where deemed as a requirement (as per risk assessment), then high visibility vests shall be worn.
10. Monthly inspection records of PPE must be kept in the Safety file
11. The contractor shall provide training to his/her employees on the correct use, care and maintenance of PPE and keep the record.

3.39 Confined Spaces

1. The contractor shall ensure that they comply with the plant safety regulation (240-150642762) in relation to the confined spaces.
2. The contractor must ensure that the station rescue emergency number is always available.
3. The Principal Contractors shall develop their own confined space procedure
4. The Principal Contractor shall ensure that the confined space procedure includes provision for training (All the employees to be trained on working on confined space , atmosphere monitoring and execution of permits.
5. No personnel may enter a confined space before Eskom Kusile Power Station Safety personnel has assessed and issued gas test permit
6. Before entering a confined space, Contractor's Personnel shall obtain a Confined Space Entry Permit
7. Only Contractor's Personnel who have been properly trained on the hazards associated with confined space work shall be allowed to enter a confined space
8. The principal Contractor shall ensure that an adequate number of suitable gas monitors are available to continuously monitor the confined space during entry. Before entering the confined space, all persons shall be given a briefing as to the precautions that must be taken.
9. While work is being performed in the confined space, a person with basic first aid training shall be immediately available to render emergency assistance if there is reason to believe that a hazard may exist in the space or if a hazard exists.
10. When the work in the confined space is completed, the person authorizing entry into the confined space shall verify that all persons have exited the confined space and that it is safe to remove the permit. The authorizing person shall then sign, date, and write in the time the permit was removed.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

11. Electric welding, gas welding, cutting, or any other hot work shall not be performed on the interior or exterior, or near the openings of any confined space which may contain flammable or explosive gases or vapours until the space has been properly cleared
12. The contractor shall ensure that they comply with the plant safety regulation (240-150642762) in relation to the confined spaces.
13. The contractor must ensure that at least one person or there is a responsible person who is trained on work that will be carried in the confined spaces, also to rescue and conduct the risk assessment.
14. The contractor must ensure that the station rescue emergency number is always available.

3.40 Incident Investigation

All incidents shall be investigated in terms of OHS Act General Administrative Regulations 8 and 9, using Eskom Kusile Power Station Procedure 32-95 OHS incident management as a reference, and where injuries as contemplated in sections 24 and 25 have been sustained, be reported to the Department of Employment and Labour.

Contractors shall use the Eskom Kusile Power Station Flash report to report incidents immediately or before end of shift. The standard General Administrative Regulation Annexure 1 “Recording of an Incident form” for all incident investigation reports. The objective of incident investigation should not only be a legal requirement but should establish why and how the incident occurred and find out the real root cause of the incident and to decide on precautionary measures that are required to address the root cause to prevent any further recurrences of the same or similar incidents.

A**ll incidents shall be Reported to the Client Immediately and reported on Sap EHS within 24 hours and investigated within 7 days.**

3.41 Emergency Management

The art of emergency preparedness and response is to minimise the effects of any emergency and to restore normal activities as soon as possible. The contractor must develop and align their own Emergency response plan with Eskom Kusile Power Station’s to address any emergency which might arise at any given point in time. The contractor to familiarise themselves with the Eskom Kusile Power Station emergency response plan and procedure. Periodic emergency drills must be undertaken to test the effectiveness of their plan. This must be recorded and provided on request.

3.42 Non-Conformance and Compliance

1. Any non-compliance to any health and safety requirement in this OHS specification is subject to discipline in terms of the Eskom Kusile Power Station Procurement and Supply Chain Management Procedure.
2. Main contractors are required to implement a non-conformance procedure (if not already in place) for issuing to contractors for transgressions. The procedure can include “quality” related non-

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

conformance issues. Similarly, appointed contractors must implement a non-conformance procedure.

3. The procedure for the issuing and closing off of non-conformance reports shall be strictly adhered to.
4. Contractor project management must monitor the close out of non-conformances issued, in not doing so; any recommendations made may not be implemented.
5. Where non-conformances are issued by Eskom Kusile Power Station then one of the close-out steps of the procedure will be for the offender to be called by the responsible project manager to explain the non-conformance issued and what plan is in place to prevent a recurrence of the non-conformance.
6. Should the contractor fail to provide adequate PPE (as per PPE standards) to their employees for the tasks being performed and/or to visitors; failure to enforce the wearing of such PPE will be viewed as a transgression of the legislative and Eskom Kusile Power Station requirements.

3.43 OHS Files

1. OHS file means documents or records in permanent form, containing the information about the safety and health management system from inception, execution to completion of works.
2. All contractors are required to keep the OHS file on every project site. If there is more than one site per project, a file per site shall be kept at that site. Contractors may keep additional files at their head office as additional records. The OHS file shall be maintained by all the contractors on their project sites and shall be available on request for audit and inspection purposes.
3. The OHS file shall consist of the OHS documentation/information in line with the OHS requirements/specification, legal and other requirements.
4. The sequence of filing the documentation must be kept in the same sequence as listed in this OHS requirements /specification and the OHS plan.
5. Each record shall be separated by partitions to afford easy identification and access. Each partition must be labelled.
6. On completion of the work/project, the main contractor must hand over a consolidated health and safety file to the project manager.
7. In case where the project is extended, should the documentation in the OHS files become cumbersome, the older documentation must be archived in boxes which shall be correctly labelled and be available for auditing purposes. The archived documentation must be handed over at the completion of the project.

3.44 Work Stoppage

1. Any person may stop any activity where an unsafe act or unsafe condition that poses or may pose an imminent threat to the safety and health of an individual or create a risk of degradation of the environment. This includes any unauthorised work or service performed by, or legally or contractually non-compliant acts or omissions by, any contractor contracted to work at that site.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

2. Work stoppages that are initiated due to OHS concerns, non-compliance, or poor performance related to the contractor's works or services shall not warrant any financial compensation claim lodged against Eskom Kusile Power Station where the contractor has not met the requirements defined legally or contractually.
3. Where stoppages are carried out, the required non-conformance report shall be raised.
4. All work stoppages ideally should be investigated and documented by contract custodians.

3.45 Hours Of Work

The requirements of the Basic Conditions of Employment Act, Chapter Two "Regulation of Working Time" must be adhered to. All contractors are required to maintain an accurate record of time worked by each employee.

3.45.1 Normal Work

All work conducted on site shall fall within the legal requirements in accordance with the Basic Conditions of Employment Act. Contractors will notify their Eskom Kusile Power Station Supervisor or project manager of any work that needs to be performed after hours according to the agreed arrangements. (The application needs to be submitted timeously). Where applicable, the notification should include proof of application, for overtime, to the Department of Employment and Labour and /or the letter of approval from the Department of Employment and Labour.

3.45.2 Night Work

When night work is to be performed, the baseline risk assessment must be reviewed to include the management of night work. Contractors shall provide sufficient lighting to enable the entire work site to be illuminated to a degree that employees will not work in dark (un-illuminated) or dimly lit areas. Care must be exercised as not to use few lights with high light intensives as this will cause night blindness.

If work is continuing from day light into night, at dusk, a tool box talk must be held where all employees will be advised of the hazards of night work and the extra precautions which require to be taken, i.e. poor housekeeping, stepping on uneven ground, stepping into holes etc.

3.45.3 Overtime

When overtime is required to be performed, The Main contractor shall inform the Eskom Kusile Power Station Contract manager of such function and provide proof of exemption from the Department of Employment and labour. Contractors shall be aware of the effects of human fatigue and regulate overtime accordingly. The baseline risk assessment must be reviewed to include the management of overtime work.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

3.46 Omissions From Safety and Health Requirements Specification

By drawing up this OHS specification Eskom Kusile Power Station has endeavoured to address the most critical aspects relating to OHS issues in order to assist the contractor to adequately provide for the health and safety of employees on site.

Should Eskom Kusile Power Station not have addressed all OHS aspects pertaining to the work that is tendered for, the contractor needs to include it in the OHS plan and inform Eskom Kusile Power Station of such issues when signing the contract.

3.47 Contract Sign Off

On completion of the project, all Eskom Kusile Power Station team must conduct the final audit, inspections, and housekeeping to identify defects, outstanding actions, and open incident cases, and present their findings to the contractor and Eskom Kusile Power Station contract manager, who must facilitate the closeout. Once the contractor has closed all findings the Eskom Kusile Power Station's team will verify and sign off prior to issuing a completion certificate and final payment.

3.48 Eskom Kusile Power Station 'S Right to Terminate the Contract

The contractor/supplier shall at all times comply with Eskom Kusile Power Station 's occupational health and safety (OHS), legal and other requirements as amended for the duration of the contract. In addition, the contractor shall comply with the requirements contained in the SHE Specification. Eskom Kusile Power Station reserves the right to terminate the contract in the event that the contractor has built up a history of poor performance or non-conformance in relation to matters of Eskom Kusile Power Station OHS and legal compliance. No work may commence until the health and safety file has been approved by Eskom Kusile Power Station OHS personnel.

3.49 Barricading

Kusile Power Station has a legal obligation under the Occupational Health and Safety Act to ensure a work environment that is free from harm. Furthermore, Kusile Power Station also has an obligation to protect our co-workers, Business Partners (contractors) and members of the public, from hazards arising from any of the stations' activities. The need to barricade a work area may arise from the following identified hazards but not limited to: Falling objects or flying objects due to work at heights Falls into open trenches or excavations Exposure during radiation work Containment of hazardous chemical substances Contact with hot surfaces Burns and Eyes impairment from hot work operations or activities Exposure to risk of explosion

Prohibited Barricading material:

The danger tape (red and white) is prohibited as the means of barricading. **Only** the emergency team can use this type of barricading in cases of emergency.

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

The following requirements needs to be adhered to, at all times:

1. Barricading shall be fitted with a tag which shall have the following information clearly displayed:
2. Name of the department or Contractor Company,
3. Name of the responsible person and contact number, frequency of barricading inspection.
4. A warning sign shall be displayed informing people of the existence of the unsafe conditions.

The above information must be clearly attached to the barricade until the activity is completed and the barricading is safely dismantled

1. Only solid barricading shall be allowed for activities longer than 7 days
2. All safety netting barricades must be supported
3. Under no circumstances must a barricaded area be accessed without the required authorization from the activity supervisor/responsible person. **Unauthorized entry into a barricaded area is a violation of a safety rule and may lead to disciplinary measures**.
4. Never modify any constructed solid barricading to suit your own conditions as this is viewed as tempering. Contact the relevant person/s should such a need arise.
5. There must be adequate lighting in barricaded areas.
6. Climbing over solid barricading is prohibited and is considered a safety rule violation.
7. All barricading should be erected at a sufficient distance away from the hazard to prevent physical contact being made between personnel or equipment and the hazard.
8. The Supervisor of the work being conducted is accountable for ensuring that a risk assessment is conducted before the commencement of work and selecting the appropriate controls in relation to temporary barricading where the work will result in a hazard that may affect others.

3.50 Contractor Performance Monitoring

Contractor management is required to do the following as part of the continuous improvement initiatives:

1. Visible Felt leadership by top management
2. Identify critical tasks and monitor by conducting Job Observations
3. Contractor Chief Executive or Managing Director shall present the lost time incidents at Kusile Power Station Mancom meeting
4. BSO Weekly by Site Manager , Supervisors and Safety Officer
5. Job Observations by supervisors weekly

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.

6. Submit weekly housekeeping report inspection
7. Submit OHS statistics monthly 1st day of the month

4. Authorization

1. Thobile Yonga
2. Thami Simelane

5. Revisions

Date	Rev.	Compiler	Remarks
September 2026	1	Xolile Langa	New issued Scope for Coal, Ash, Limestone and Gypsum Mechanical Maintenance Services

6. Development Team

Nkhetheni Ramukosi

Controlled Disclosure

When downloaded from the document management system, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.

No part of this document may be reproduced without the expressed consent of the copyright holder, Eskom Holdings SOC Ltd, Reg No 2002/015527/30.